



PRODUCT BROCHURE

CAPAMA PRINTING MACHINERY COMPANY LIMITED

CAPAMA PRINTING MACHINERY COMPANY LIMITED | NO.2011, ZHAOCHONG RD, CHONGGU
TOWN, QINGPU, SHANGHAI, CHINA POSTAL CODE: 201706 TEL: +86-21-34654695 INTERNATIONAL
HOTLINE: TEL: +86-13817667267 E-MAIL: INFO@CAPAMA.COM E-MAIL: ANNA.WANG@CAPAMA.COM
E-MAIL: MURRAY.OWEN@CAPAMA.COM

Specification

CPM-520SXT-IR

Max. Web Width	520 mm
Max. Printing Area	650(L) x 500(W)
Max. Speed	5000imp/hr
Machine Dimensions	L 650x W 170 x H 165 (cm)
Machine Weight	2600 KG(N.W.) , 3000KG(G.W.)
Advantages	<ul style="list-style-type: none"> • <i>CNC control system allows user input via wide TFT color HMI touch screen. Fast and convenient. Other languages can be entered into the HMI touch screen using English letters.</i> • <i>Independent servo drive printing station with specialize precise linear sliding tracks for printing head vertical and horizontal movement. Vacuum suction base on printing station make printing web no flutter.</i> • <i>Adjusting scraper pressure and screen frame angle are both simple operations.</i> • <i>2nd pass scanner unit is available for multi-color printing, computer</i>

will auto-adjust the registration while printing, no need for manual operation. 2nd pass scanner hole punching unit benefits 2nd pass scanner read, especially for special jobs.

- *Pneumatic printing plate lifting, pneumatic squeegee adjustment*
- *Material pull-scraping protection wheel, more suitable for thin film printing*
- *More accurate pneumatic punching set*
- *Actuating control on printing bed with setting for increased accuracy and flexibility*
- *Dual printing guarantees thickness of ink layer.*
- *Online sunlight testing; a more humanistic design*
- *Inter-reverse use of squeegee, saving material and work time*

Standard
Unit

- *Paper Feeding Machine*
- *2nd pass scanner unit*
- *Standard unit*
- *Computer servo control system from Japan*
- *Adding suction device to the feeder parts*
- *215 scraper and covering ink blade*
- *7.265 scraper and covering ink blade*
- *Screen Frame*

Optional
Unit

- *UV Dryer*
- *Vacuum Chuck (adjust the pressure)*
- *CPM-320F CNC High speed Single station Die-cut(hot-stamping)Machine*
- *CTR-20M Circuits Tunnel Heat Dryer*

Applicable
Materials

Art paper, Mirror coat paper, Foil paper, PET, PVC, PP, PE, Electrostatic paper, Hologram (Laser) film, Phosphorescent film, Flockings paper, Binding cloth, Textile, Garment, Satin, Ribbon, Cardboard, Kraft, Crepe paper, Polar film, Diffuse film, Silver reflect film, Aluminum foil, Laminate copper foil, Photoelectric film, Conductor film, Soft PC plate, LCD conductor glue, Shockproof glue, High Tec. Laminate material, EMI insulator, Sponge rubber, Conductor Sponge rubber, Thermal paper, PE, Plastic Leather, Thin film (IMD), Nameplate, Heat transfer labels, Glue side printing labels, Security labels...etc materials in roll.